



# BOVA

## CORE RANGE

## FALL ARREST SYSTEM



FALL ARREST  
SYSTEM

CODE: HARN01220

**Sizing**  
One size fits all

**Weight**  
2,00kg

**Standards**  
SANS 50354 | EN 354  
SANS 50355 | EN 355  
SANS 50361 | EN 361  
EN 362



### STANDARD HARNESS FEATURING:

- Permanently attached, double leg, shock absorbing lanyard with scaffolding hooks
- Adjustable leg & chest straps

### DESCRIPTION:

This is a standard harness with non-specialised features and is recommended for those who need to navigate obstacles while working at heights. The double leg lanyard improves safety to the wearer by allowing them to remain attached to at least one anchor point at all times, through the use of one hook, while moving the second hook around the obstacle to a new anchor point. The adjustable leg straps improve safety to the wearer through a customised fit.

### MATERIALS:

- Harness Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
- Lanyard Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
- Lanyard length: 1750mm
- Lanyard length when shock absorber is fully elongated: 3 450mm
- Chest Strap:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
- Buckles:** • Interlocking, corrosion-resistant steel buckles
- Hooks:** • Corrosion-resistant steel scaffolding hooks with 50mm gate opening

This product is manufactured in South Africa by Quality Safety, a subsidiary of BBF Safety Group (Pty) Ltd. In an ISO 9001 accredited factory.

July 2021

