

**BOVA****FALL ARREST  
LANYARD**

# LANYARD

## EXTENSIO RANGE

**CODE: LANY01620****Sizing**  
1750mm**Weight**  
1.65kg**Max Fall Weight**  
140kg**Standards**  
SANS 50354 | EN 354  
SANS 50355 | EN 355  
EN 362

### LANYARD FEATURING:

- Elasticated double leg with scaff hooks
- Single leg with snap hook
- Shock absorber



### DESCRIPTION:

This is an elasticated double leg, shock absorbing lanyard with two scaffolding hooks and a single snap hook connector that is engineered to attach to a dorsal D-ring on a stand-alone, fall arrest harness.

The elasticated lanyard lifts the hooks off the ground when not in use, reducing the wear and tear caused to hardware when dragged on the ground. It further improves safety to the wearer by reducing the potential of the lanyard being caught in dangerous machinery.

This lanyard is recommended for those who are required to navigate obstacles whilst working at heights. The double leg lanyard improves safety to the wearer by allowing them to remain attached to at least one anchor point at all times, through the use of one hook, while moving the second hook around the obstacle to a new anchor point.

The built-in shock absorber is engineered to reduce the total force experienced in a fall to a survivable force of less than 6kN.

### MATERIALS:

**Webbing:**

- 25mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes

**Lanyard length:**

- 1750mm when shock absorber is intact
  - 3450mm when shock absorber is fully deployed

**Hooks:**

- Corrosion-resistant steel hooks:
  - Scaffolding hooks: 50mm gate opening that can withstand a force of 23kN
  - Snap hook: 20mm gate opening that can withstand a force of 22kN

This product is manufactured in South Africa by Quality Safety, a subsidiary of BBF Safety Group (Pty) Ltd. in an ISO 9001 accredited factory.

**January 2021**