

Sydney / 51005

Single Density Polyurethane Sole

Manufactured with direct injection-moulded single density polyurethane, this range is suited to light industrial environments.

Sex	Sizes	Colour	Accreditations
Female	3 - 8	Black / Brown	SANS/ISO 20345



Standard Fit

- Upper:**
- Cut from 2.0 - 2.2mm Full Grain Leather
 - Featuring a pull-strap and elastic side gussets for ease of entering and exiting the boot
- Lining:**
- The vamp lining is from a hi-tech needle-fibre blend with excellent perspiration absorbency and is treated with *Ultra-Fresh** to impart hygienic and anti-bacterial properties to the material
- In-Sock & Top Sock:**
- The in-sock is from an anti-static non-woven material
 - The Energiser top sock is from a combination of polyester and wool, with excellent perspiration absorbency
 - The top sock features EVA foam inserts on the ball and heel area for enhanced comfort and shock absorption
 - The top sock has been treated with *Ultra-Fresh** to impart hygienic and anti-bacterial properties to the material
- Sole:**
- The sole is from a single density Polyurethane with a shore hardness of 0.64mm - 0.65mm
 - A shank reinforcement is moulded into the midsole for additional arch support
 - This boot can withstand temperatures of up to 95°C
 - This boot is anti-static
- Toe Cap:**
- Steel toe cap
 - Can withstand an impact of 200 joules
 - If required, this shoe is available without a steel toe cap - 51505

The Sydney boot has been tested to comply with SANS/ISO 20345 specifications and carries the SANS/ISO 20345 certified mark

This product is manufactured in South Africa by BBF Safety Group (Pty) Ltd. in an ISO 9001:2000 accredited factory.

NRCS/9002/28776/0135
FEBRUARY 2020