


LEATHER WELDING GLOVE WELD/RED





EN 388: 2016



WELD/RED

Description

Dromex® WELD/RED elbow length protection leather thermal gloves are designed for use in high heat and welding related operations. Consists of premium grade, red dyed, cow split leather, with a fully cotton lined palm and fingers, gunn cut, apron palm, for added thermal finger protection, wing thumb and sewn with Kevlar thread.

Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

Compliance & Conformity

Complies with the requirements of CE type examinations EN 420 for innocuousness, pH value >3,5 <9,5, Chromium VI in leather shall not exceed 3,0 mg/kg and the size is correct. Approved with directive 89/686/EEC, EN388:2016 Mechanical Risks.

Complies to, but not approved to EN 407:2004 Thermal Risks for Heat & Flame and EN12477:2001+A1 2005 Welding Gloves (A).

Quality System conforms to ISO 9001:2008 and environmental management system, ISO 14001:2015 system certificated or acceptable equivalent.

Specifications

Style: Apron palm, gunn cut, wing thumb

Liner: Lined in black cotton fleece

Palm: 2.71mm \pm 5%, Apron palm is 1.36mm \pm 50%

Back: $2.71 \text{mm} \pm 5\%$

Cuff: 8-inch Red split leather cuff
Mass: ± 350g Per pair (size 11/12)

Packaging, Storage & Obsolescence

WELD/RED - Packed 12 pairs per bundle and 60 pairs per carton for shipping. Store in a cool, dry place. Stored correctly, the gloves physical properties will not change for up to three years.











Cleaning & Maintenance

Gloves should not be left in a contaminated condition if re-use is intended, especially if potential hazards exist. Before removal from the hands, excess contaminant should first be removed from the gloves.

Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands.

How to decontaminate your leather glove.

Under no circumstances should leather submerged in water.

- 1. Prepare a lukewarm water solution using mild detergent.
- 2. Gently wipe your leather glove with a cloth.
- 3. In- rder to reduce stiffering, allow the leather glove to dry naturally.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.A

Size Available

Code	Size	Palm Length
WELD/RED	L/10.5	130mm (±5mm)

- * As per the EN420 standard, actual measurement of gloves are determined by the manufacturer, taking into account the behaviour of the glove material, its thickness (such as leather gloves, PVC gloves etc), elasticity and the intended use.
- * Sizing charts only serve as a guide. Sizes and measurements are for reference only. In order to make an informed decision, always try on the gloves as each glove features a unique construction to accomodate a wearer's preferences.

Marking

Measurement Guide



Materials



- 1. Winged thumb
- 2. Gunn cut
- 3. Apron palm
- 4.8 inch cuff

Dromex: Unit 1, 1 Blase Road, New Germany, 3620, South Africa T. +27(31) 713 1960 E. info@dromex.co.za www.dromex.co.za