



SGL106

Crossover™ ANSI • CSA •



VENTED FRAME



INCLUDES STRAP

Removable indirect vented rolled rubber gasket // Adjustable detachable strap with quick release // Custom imprinting available



Black and Gray Frame | 3 Variations

- SBG10610DT ●●● Clear H2X AF
- SBG10620DT ●●● Gray H2X AF
- SBG10680DT ●●● I/O Mirror AF

Gray and Lime Frame | 1 Variation

- SGL10610DT ●●● Clear H2X AF

Part No.	Lens Marking	Temple Marking
SBG10610DT	P Z87 + U6	P Z87 + / P c SEI Z94.3
SBG10620DT	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SBG10680DT	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
SGL10610DT	P Z87 + U6	P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

General Specifications

Weight: 32.9 gm
 PD: 64 mm
 Bridge: 13.6 mm
 Lens base: 9 curve
 Lens size diagonal: 78.6 mm
 Lens size vertical: 46.8 mm
 Lens thickness: 2.0 mm
 Overall length (lens - tip): 170 mm
 Overall width (hinge - hinge): 130.5 mm
 Closest point between temple tips: 83 mm
 Closest point between lens: 9.5 mm
 Strap Length: 165 - 195 mm

Materials

Lens: polycarbonate
 Rubber gasket: polycarbonate & thermoplastic rubbers (TPR)
 Temples: polycarbonate
 Temple strap: polyester
 Hook for temple strap: nylon
 Takeup loop for strap: nylon



WATCH THE
CROSSOVER
 VIDEO