


# Dromex



## MIIZU300HI GLOVE



MIIZU300HI



### Description

Dromex® MIIZU300HI, high-visibility yellow polyester lined gloves reinforces the PU (Polyurethane) and nitrile water based micro foam finish. Designed for general handling, electronic assembly, computer assembly, automotive assembly, truck, forklift and crane driving and small parts handling.

Water based polyurethane gloves provide users with enhanced comfort and dexterity.

### Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

### Compliance & Conformity

Complies with the requirements of CE type examinations EN 420 for innocuousness and EN 388 for compliance with directive 89/686/EEC Mechanical Risks (3,1,3,1).

Quality System conforms to ISO 9001:2008 and environmental management system ISO 14001:2015 system certificates or acceptable equivalent.

### Specifications

Style:	High visibility, yellow palm dipped
Liner:	Polyester
Palm:	PU and nitrile coated on liner 1.1mm ± 5%
Back:	0.9mm ± 5%
Cuff:	Polyester
Mass:	±55 g per pair (size 11)

### Sizes Available

8-11

### Packaging, Storage & Obsolescence

Packed in individual bags and sold as 240 pairs per carton for shipping. Store in a cool, dry, dark place.


Stored correctly, the gloves physical properties will not change for up to three years.



### Cleaning & Maintenance

Gloves should not be left in a contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed from the glove. Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands.

The gloves may then be decontaminated as indicated below.



We recommend that no bleaching or oxidising ingredients or any fabric softeners be used. Recommended washing temperature is up to 40°C with mild detergents. The drying process may cause felting on the fabric surface. Drying temperature should not exceed 70°C (158°F).

There is no remarkable impact on cut resistance during the normal life cycle of a glove. Depending on glove construction, staining and cleaning method, the differences in shrinkage, yarn strength and colour may occur.

In order to maximise the glove life cycle, we recommend the mildest possible cleaning conditions in terms of temperature, chemicals and cycle duration.

### Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.

### Materials



1. Palm dipped with PU & nitrile
2. Polyester wrist cuff

### Marking

