

f www.lemaitre.co.za Sourced and manufactured in South Africa

SPECIFICATION SHEET



RAPTOR RANGE

8024 - Steel Toe Cap Size: 5 - 12 Sex: Male Colour: Black and grey



ALSO SEE: 8034 - STEEL MIDSOLE

UPPER

- Combination of Nuback and Smooth Buffalo Full-grain leather.
 - Nubuck 1.8mm 2.0mm leather
 - Smooth Buffalo 1.9mm 2.1mm
- Durable Black Condor Nylon fabric in collar, tongue and side panels for enhanced breathability and comfort.
- Toe and Heel scuff for enhanced durability.
- 19mm padded collar and 10mm padded bellows tongue for enhanced comfort and ankle support.
- Heel stiffener for shape longevity.
- Punch detail in vamp and quarter areas for enhanced breathability.
- 4 pair plastic lace-guides.
- 110cm black braided nylon laces with central core for additional strength.

IN-SOCK & TOP SOCK

- Anti-static in-sock is made from 2mm non-woven material.
- The top sock is made from a durable polyester material that offers abrasion resistance and is quickdrying in nature. The top sock is treated with Ultra-Fresh technology to impart anti-bacterial and antistatic properties to the material. The top sock contains anti-static stitching and has been treated with a lemon scent for lasting freshness.

COMPONENT SPECIFICATIONS

LINING

- The vamp lining is made from non-woven synthetic fibre for enhanced comfort and breathability.
- The quarter and tongue lining are made from red ferrabelle non-woven material laminated to 4mm foam for enhanced comfort and breathability.

TOE CAP

- Steel Toe Cap.
- Can withstand an impact load of 200 joules.

SOLE

- Shank reinforcement for additional arch support.
- The Raptor sole is made from Double Density PU/PU.
- The midsole is made from a flexible low density Polyurethane with a shore hardness of 45 – 55.
- The outer sole is made from a hardwearing Polyurethane with a shore hardness of 55 – 70.
- Built in TPU inserts for additional support and torsion control.
- The shoe can withstand temperatures up to 95°C.
- The boot has SRA rated slip-resistance.
- The boot is anti-static.
- Also available with a Steel Midsole 8034 for superior protection against sharp objects penetrating the sole.



f www.lemaitre.co.za Sourced and manufactured in South Africa

SPECIFICATION SHEET



RAPTOR RANGE

8034 - Steel Midsole Size: 5 - 12 Sex: Male Colour: Black and grey



ALSO SEE: 8024 - STEEL TOE CAP

UPPER

- Combination of Nuback and Smooth Buffalo Full-grain leather.
 - Nubuck 1.8mm 2.0mm leather
 - Smooth Buffalo 1.9mm 2.1mm
- Durable Black Condor Nylon fabric in collar, tongue and side panels for enhanced breathability and comfort.
- Toe and Heel scuff for enhanced durability.
- 19mm padded collar and 10mm padded bellows tongue for enhanced comfort and ankle support.
- Heel stiffener for shape longevity.
- Punch detail in vamp and quarter areas for enhanced breathability.
- 4 pair plastic lace-guides.
- 110cm black braided nylon laces with central core for additional strength.

IN-SOCK & TOP SOCK

- Anti-static in-sock is made from 2mm non-woven material.
- The top sock is made from a durable polyester material that offers abrasion resistance and is quickdrying in nature. The top sock is treated with Ultra-Fresh technology to impart anti-bacterial and antistatic properties to the material. The top sock contains anti-static stitching and has been treated with a lemon scent for lasting freshness.

COMPONENT SPECIFICATIONS

LINING

- The vamp lining is made from non-woven synthetic fibre for enhanced comfort and breathability.
- The quarter and tongue lining are made from red ferrabelle non-woven material laminated to 4mm foam for enhanced comfort and breathability.

TOE CAP

- Can withstand an impact load of 200 joules.
- Also available with a Steel Toe Cap 8024.

SOLE

- Shank reinforcement for additional arch support.
- The Raptor sole is made from Double Density PU/PU.
- The midsole is made from a flexible low density Polyurethane with a shore hardness of 45 – 55.
- The outer sole is made from a hardwearing Polyurethane with a shore hardness of 55 – 70.
- Built in TPU inserts for additional support and torsion control.
- The shoe can withstand temperatures up to 95°C.
- The shoe is available with a steel midsole for superior protection against sharp objects penetrating the sole.
- The boot has SRA rated slip-resistance.
- The boot is anti-static.