

Paris / 51003

Single Density Polyurethane Sole

Manufactured with direct injection-moulded single density polyurethane, this range is suited to light industrial environments.

Sex	Sizes	Colour	Accreditations
Female	3 - 8	Black	SANS/ISO 20345



Standard Fit

Upper:	<ul style="list-style-type: none"> • Cut from 2.0 - 2.2mm Full Grain Leather • 20mm Padded collar for enhanced comfort and support • Elastic side gussets for ease of entry and exit of the shoe
Lining:	<ul style="list-style-type: none"> • The quarter lining is from an industrial ferrabelle non-woven material • The vamp lining is from a hi-tech needle-fibre blend with excellent perspiration absorbency and is treated with <i>Ultra-Fresh*</i> to impart hygienic and anti-bacterial properties to the material
In-Sock & Top Sock:	<ul style="list-style-type: none"> • The in-sock is from an anti-static non-woven material • The Energiser top sock is from a combination of polyester and wool, with excellent perspiration absorbency • The top sock features EVA foam inserts on the ball and heel area for enhanced comfort and shock absorption • The top sock has been treated with <i>Ultra-Fresh*</i> to impart hygienic and anti-bacterial properties to the material
Sole:	<ul style="list-style-type: none"> • The sole is from a single density Polyurethane with a shore hardness of 0.64mm - 0.65mm • A shank reinforcement is moulded into the midsole for additional arch support • This shoe can withstand temperatures of up to 95°C • This shoe is anti-static
Toe Cap:	<ul style="list-style-type: none"> • Steel toe cap • Can withstand an impact load of 200 joules • If required, this shoe is available without a steel toe cap - 51503

The Paris shoe has been tested to comply with SANS/ISO 20345 specifications and carries the SANS/ISO 20345 certified mark

This product is manufactured in South Africa by BBF Safety Group (Pty) Ltd. in an ISO 9001:2000 accredited factory.

[NRCS/9002/287766/0132](#)

FEBRUARY 2020