

TruLock™ ANSI • CE • CSA •



LOCKING
TEMPLE



DIELECTRIC

Dielectric // Lightweight spectacle – 21 gm
// Patented temples lock into place // Custom
imprinting available

Black Temples | 8 Variations

- SB9510S • • • Clear
- SB9510ST • • • Clear **H2X** AF
- SB9520S • • • Gray
- SB9520ST • • • Gray **H2X** AF
- SB9530S • • • Amber
- SB9556S • • • Multi-color Mirror
- SB9580S • • • I/O Mirror
- SB9580ST • • • I/O Mirror AF



WATCH THE
TRULOCK
VIDEO

TruLock Multi-Colors ANSI • CE • CSA •

Sold in dozen quantity only // Comes with six assorted temple colors: red, blue, green, purple, orange and black // Multi-pack includes two of each temple color // Perfect for work areas where color coding is necessary // Custom imprinting available

Multi-Color Temples | 2 Variations

- S9510SMP • • • Clear
- S9520SMP • • • Gray



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SB9510S	P Z87 + U6	P Z87 + / P c SEI Z94.3	Weight: 21 gm	Lens: polycarbonate
SB9510ST	P Z87 + U6	P Z87 + / P c SEI Z94.3	Bridge: 11.3 curve	Temples: nylon
SB9520S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	Lens base: 9.5 curve	Hinge: nylon
SB9520ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	Lens size diagonal: 132.7mm	
SB9530S	P Z87 + U6	P Z87 + / P c SEI Z94.3	Lens size vertical: 44 mm	
SB9556S	P Z87 + S	P Z87 + / P c SEI Z94.3	Lens thickness: 1.8 mm	
SB9580S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3	Overall length (lens - tip): 157 mm	
SB9580ST	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3	Overall width (hinge - hinge): 130 mm	
S9510SMP	P Z87 + U6	P Z87 + / P c SEI Z94.3	Closest point between temple tips: 65 mm	
S9520SMP	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3		

Lens Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

S: Special Purpose

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices