



### **000 Series** 6

## SABS Moulded Adjustable Maintenance Free Respirator With or Without Comfort Exhalation Valve

Electrostatic charged filter media with superior lower breathing resistance

Effectively reducing heat and CO2 build up resulting in higher worker productivity and comfort.

Manufactured under SABS Mark scheme

If you cannot see the mark on the product, it is because it does not have a SABS mark scheme permit!

Don't be fooled by products claiming to be SABS "Approved" only products with the SABS Mark on are authorised and approved to do so.

# Made in South Africa

- •
- •
- Designed To Suit Local Conditions Made by South Africans No Continuous Price Increases Due To Exchange Rate Fluctuations

Base Metal Manufacture Brick Manufacture Laboratories **Powdered Additives** Pharmaceutical Powdered Chemicals Sawmills Food Industry Textile industry Craftwork Iron and steel industry Mining Underground civil engineering Woodworking Welding work







6200







For further information or technical specifications contact us on Tel: 086 1000 545 Email: sales@greenline-sa.com Web: www.greenline-sa.com



All respirators are manufactured in South Africa accordance with international standards and quality approvals.

GreenLine is ISO9001 accredited by TUV Rhineland in Germany

Punched and Rounded Metal Nose Clip No wires to punch through and injure users

Pull tabs to fit any size

No Staples to pull loose or scratch users

To exhaust exhaled air. Effectively get workers to wear masks in hot areas Resulting in higher worker productivity and comfort

Respirators can provide lower level protection against solid and liquid aerosols and smoke containing the following materials such as: Calcium carbonate / China clay / Cement / Cellulose / Sulphur / Cotton / Flour / Carbon / Ferrous metals / Hardwood / Glass fibres / Plastic / Vegetable oils/ Mineral oils / Quartz / Copper / Aluminium / Bacteria / Europi and mycobacterium ninium / Bacteria / Fungi and mycobacterium erculosis (T.B.) tub

P1 has an Assigned Protection Factor (APF) of 4, FFP2 has an APF of hd an FFP3 has an APF of 20. Selection of the most appropriate rator depends on the contaminant and Occupational Exposure Level and guidance should always be sought.

