



**LEMAITRE**  
SAFETY FOOTWEAR



## TORSION CONTROL **EAGLE** RAPTOR RANGE

STEEL TOE CAP | 8025  
SOLE: RAPTOR SOLE | SIZE: 5-12  
SEX: MALE  
COLOUR: BLACK AND GREY

### FEATURES OF THE EAGLE:

#### UPPER

- Full-grain leather upper for enhanced durability.
- Combination of Nubuck and Smooth Buffalo Full-grain leather.
  - Nubuck - 1.8mm - 2.0mm leather
  - Smooth Buffalo - 1.9mm - 2.1mm
- Durable Black Condor Nylon fabric in collar, tongue and side panels for enhanced breathability and comfort.
- Anti-toe and heel scuff for enhanced durability.
- Padded collar for improved comfort.
- Padded bellows tongue for added comfort and enhanced defense against debris entering the boot.
- Heel stiffener for shape longevity.
- Punch detail for enhanced breathability.
- 3 sets lace guides and 3 sets metal hooks.
- 140cm black braided nylon laces with central core for additional strength.

#### IN-SOCK & TOP SOCK

- Anti-static in-sock is made from 2mm non-woven material.
- The top sock is made from a durable polyester material that offers abrasion resistance and is quick-drying in nature. The top sock is treated with Ultra-Fresh technology to impart anti-bacterial and anti-static properties to the material. The top sock contains anti-static stitching.

#### LINING

- The vamp lining is made from non-woven synthetic fibre for enhanced comfort and breathability.
- The quarter and tongue lining are made from red Cambriil non-woven material laminated to 4mm foam for enhanced comfort and breathability.

#### TOE CAP

- Can withstand an impact load of 200 joules.
- Also available with a Steel Toe Cap - 8024.

#### SOLE

- Shank reinforcement for additional arch support.
- The Raptor sole is made from Double Density PU/PU.
- The midsole is made from a flexible low density Polyurethane with a shore hardness of 45 - 55.
- The outer sole is made from a hardwearing Polyurethane with a shore hardness of 55 - 70.
- The boot can withstand temperatures up to 95°C.
- The boot has SRA rated slip-resistance.
- The boot is anti-static.

**FROM ONE WORKER  
TO ANOTHER**

