

Dromex



ULTI-CHEM CHEMICAL GLOVE



ULTICHEM

EN 388:2016
+A1:2018



4121X

EN ISO 374-5:2016



EN ISO 374-1:2016
A1:2018
TYPE A



JKLOTP



X1XXXX



Description

Dromex® ULTICHEM, triple coated nitrile gloves, protects the hands against chemicals, mechanical risks, contact heat (at a temperature of 100°C for 15 seconds) and microorganism risks.

The innovative ultralight, T-TOUCH triple coated nitrile micro foam technology, features the following:

- Prevents finger print residue and protects products from material contamination.
- Are easy to put on and take off.
- Has superior dexterity and enhanced grip in oily and wet applications on palm and fingers.
- Long wrist cuff, ideal for dipping of hand applications.
- Effective barrier against bacteria and fungi.

The 18 gauge nylon shell offers comfort and safety in humid conditions or acidic fluid environments.

ULTICHEM PLUS gloves are suitable for use when handling chemicals in labs, sheet metal handling, assembly work and automotive, janitorial and environmental clean-up applications and food industries.

Ulti-chem chemical protection is as follows:

Test chemical	Letter	Permeation performance levels:
Methanol	A	3
n-Heptane	J	6
Sodium hydroxide 40%	K	6
Sulphuric acid 96%	L	3
Ammonium hydroxide 25%	O	6
Hydrogen peroxide 30%	P	6
Formaldehyde 37%	T	6

Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment.

Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

Compliance & Conformity

- Complies with the requirements of CE type examinations for ISO 21420:2020 innocuousness, with a level 5 dexterity rating.
- EN 388:2016, (4,1,2,1,X) for mechanical risks.
- EN 374 – 2:2014 and EN ISO 374 -1:2016, protective gloves against dangerous chemicals.
- EN ISO 374-5:2016 protective gloves against microorganisms (uncontrolled against viruses).
- EN 407:2020 Thermal Risks (X1XXXX).
- Food grade approved in compliance with regulation (EC) No 1935/2004 and of the European Parliament, and of the Council of 27 October 2004, (EU) No 10/2011 and its amendment (EU) 2020/1245 Regulation – Specific migration of heavy metals and Overall Migration and Council of Europe Resolution AP (2004) 4 – Overall Migration.

EN 407:2020



X1XXXX


- X: Resistance to flammability (from 1 to 4)
- 1: Resistance to contact heat (from 1 to 4)
- X: Resistance to convective heat (from 1 to 4)
- X: Resistance to radiant heat (from 1 to 4)
- X: Resistance to small projections of molten metal (from 1 to 4)
- X: Resistance to large projections of molten metal (from 1 to 4)

Specifications

Style:	34.5cm, Wing thumb, Nitrile foam coated, Nitrile/water based PU, sandy finish palm and fingers with an open cuff
Liner:	18g, Nylon liner
Palm:	1.2 - 1.4mm ± 5 %
Back:	1.1 - 1.3mm ± 5 %
Cuff:	15cm Wrist cuff
Mass:	108g Per pair (size 9)

Packaging, Storage & Obsolescence


Packed in individual polybags.
Store in a cool, dry, dark place.
Stored correctly, the gloves physical properties will not change for up to 5 years.



ULTI-CHEM

Cleaning & Maintenance

Gloves should not be left in contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed. Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands.
The gloves may then be decontaminated as indicated below:



This glove is not washable.
Clean by hand using a neutral solvent with a warm damp cloth.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for.
Please consider recycling.

Sizes Available

Code	Size	Palm Length
ULTICHEM-9	M/L	111mm (±2mm)
ULTICHEM-10	L/XL	114mm (±2mm)


* As per the EN420 standard, actual measurement of gloves are determined by the manufacturer, taking into account the behaviour of the glove material, its thickness (such as leather gloves, PVC gloves etc), elasticity and the intended use.

* Sizing charts only serve as a guide. Sizes and measurements are for reference only. In order to make an informed decision, always try on the gloves as each glove features a unique construction to accommodate a wearer's preferences.

Measurement Guide



Marking



Materials



1. Wing thumb
2. Nitrile foam coated palm & fingers
3. 15cm Wrist cuff



Dromex: Cornubia Ridge Logistics Park, 30 Umganu Road,
Flanders, Blackburn, Durban, South Africa, 4319
T. +27(31) 713 1960 E. info@dromex.co.za www.dromex.co.za